sylvac

MSA	Measuring range	Resolution	Total length
15.160	**25.00 mm 1"**	0.0001 mm 0.000004"	Avec|With|Mit|Co
15.161	**25.00 mm 1"**	0.0001 mm 0.000004"	Sans|Without|Oh
	-	-	-
15.162	**50.00 mm 2"**	0.0001 mm 0.000004"	Avec|With|Mit|Co
15.163	**50.00 mm 2"**	0.0001 mm 0.000004"	Sans|Without|Oh

SYLVAC® S-DIAL PRO SMART electronic indicator.
- Maximum errorr : 1 µm
- Repeatability : 0.2 µm
- Mounting rod Ø 8 mm
- Large display with tolerance status indication by colour LED
- Output data : USB - RS232 - Bluetooth
- Three buttons, including the central button with selectable favourite function
- Wide range of functions, including MIN/MAX/DELTA
- Protection class IP51.

Travel 25 or 50 mm / 1 or 2"

Analogic dial gauges.

MSA	Measuring range	Precision	Kg
15.399	10 mm	0.01 mm	0.170

JFK FEINTASTER dial gauge on horizontal support with "Z" adjustable table.

Mitutoyo

MSA	Measuring range	Precision	Ø dial	Kg
15.126	10 mm	0.01 mm	57 mm	0.170

Analogical dial gauge MITUTOYO®.
- Circular scale : 0 - 100
- 1 dial revolution : 1 mm
- Fixing Ø 8 mm
- Carbide insert.