

LA JURASSIENNE® oil.



MSA	ml	Size	Kg
28.J.0100	100	Ø 45 x 105 mm	0.154

LA JURASSIENNE® mineral oil for wall clocks.

- Severely refined and compatible with strong oxidants
- Temperature of auto-inflammation at 200° C
- Stable product in usual stocking temperatures, manipulation and use.

Lubristyl® precision oil pen.



MSA	ml	Temp. ° C	Kg
17.210	Ø 13 x 155 mm	6 cc	0.028

Lubristyl® precision oil pen, pen shape.
Drop by drop lubricant dispenses thanks to the needle pump. Possibility to easily re-absorb the extra oil by briefly and rapidly pushing the needle.
Delivered with 6 cc oil.

Spare part :

MSA	Item	Kg
17.210-100	Oil refill, 100 ml	0.113



FOMBLIN® UT18 grease.



(1)



(2)

MSA	Colour	Packaging	Size	Kg
28.UT18-020	(1) White	Pot of 20 g	Ø 34 x 40.5 mm	0.025
28.UT18-100	(2) White	Tube of 100 g	Ø 30 x 145 mm	0.115

FOMBLIN® UT18 grease. Advantages :

- Excellent lubricant for multiple uses
- Compatible with all sorts of material like plastic, metals, glass, etc.
- It resists to oxidation and other chemical products
- Used in watchmaking for greasing gaskets
- Temperatures use range : from -30° C to +250° C.



MSA	Contents	Kg
28.001	2 g	0.030

Box with grease Fomblin® UT18.

SILCON-7® grease.



MSA	Packaging	Size	Kg
28.652	Tube of 10 g	Ø 12 x 56 mm	0.012

SILCON-7® waterproofing grease.

- For watch cases
- It stops gaskets from drying and encrusting in the thread.



(1)

MSA	Contents	Kg
28.000	2 g	0.030

Box with grease Silcon-7®.

BLASOLUBE® grease.



MSA	Type	Packaging	Kg
28.301	302	Tube of 250 g	0.277

BLASOLUBE® 302 universal lubricant grease for a very wide-ranging use.

- Soft/half-hard consistency
- Temperatures use range : from -20° C up to +150/200° C.



MSA	Type	Packaging	Kg
28.307	301	Tube of 400 g	0.460

BLASOLUBE® 301 universal lubricant grease for a very wide-ranging use.

- Soft consistency
- Temperatures use range : from -30° C up to +120/150° C.

CHRONOGREASE KLÜBER P125® grease.



MSA	Packaging	Size	Kg
28.102	Pot of 5 g	Ø 22.5 x 31 mm	0.008

CHRONOGREASE KLÜBER P125® grease.

Recommended by ETA SA for greasing mainsprings (calibres 7750, A07111, etc.).