

Universal correcting press.



MSA	Kg
13.010	1.240

Universal correcting press, facilitates the work of milling, drilling, tapping, deburring, chamfering, reaming, etc.
Wide range of tightening chucks P 4.5 type to be mounted on the broach, fine adjustment of the working height.
Large stainless steel work plate and dies adapter.
Compatible with all HOROTEC® screw-on dies.

- Contents :
- 1 press
 - 1 tip 1° angle MSA13.010-01
 - 1 tip 2° angle MSA13.010-02
 - 1 tightening chuck P 4.5 type Ø 3 mm MSA03.875-300
 - 1 dies adapter MSA13.010-AD
 - 1 ring with knurled knob MSA13.010-BA
 - 1 broach for tightening chucks P 4.5 type MSA13.010-BR
 - 1 Allen key MSA13.010-CL
 - 1 stainless steel table Ø 60 mm MSA13.010-TA.

Spare parts :

MSA	Item	Kg
13.010-01	Tip 1° angle	0.002
13.010-02	Tip 2° angle	0.002
13.010-AD	Dies adapter	0.010
13.010-BA	Ring with knurled knob	0.005
13.010-BR	Broach for tightening chucks P 4.5 type	0.020
13.010-CL	Allen key	0.001
13.010-TA	Stainless steel table Ø 60 mm	0.075

Optional tightening chucks for MSA13.010 (other Ø on request).



Ø 4.50 mm

MSA	Ø	Kg
03.875-080	0.80 mm	0.002
03.875-100	1.00 mm	0.002
03.875-150	1.50 mm	0.002
03.875-160	1.60 mm	0.002
03.875-200	2.00 mm	0.002
03.875-235	2.35 mm	0.002
03.875-250	2.50 mm	0.002
03.875-300	3.00 mm	0.002
03.875-400	4.00 mm	0.002

Tightening chuck 4.5 type.



MSA	Kg
13.010-KIT	0.096

- Kit for dial feet.
- Contents :
- 1x MSA22.558-270 : hard metal end mill , L25 mm, shank Ø 3.00, cutting Ø 2.70 mm
 - 1x MSA17.102-B : simple oiler Ø 5 mm, blue, medium needle, L70 mm
 - 1x MSA26.587-020 : instant adhesive LOCTITE 435, 20 g
 - 1x MSA99.153 : assortment of adhesive dial feet, L3 mm, 60 pieces.