

BRACELET PRESSES



MSA	Size	Kg
10.500	60 x 80 x 110 mm	0.465

Press for rapidly fitting and removing the bracelet pins and screws. Stand accessories easily accessible. The vertical guide allows a perfect alignment with bracelet screws and pins. It is equipped with a device that holds the pins holder, leaving the operator hands free.

- Contents :
- 1 press and 1 broach MSA10.500-A
 - 1 handle MSA10.504
 - 1 bracelet holder MSA10.501
 - 12 blades MSA10.502-xxx (2 of each diameter)
 - 11 pin punches MSA10.503-xxx : Ø 0.40, 0.60, 0.70, 0.80, 0.90, 1.00, 1.10, 1.20, 1.40, 1.50 and 2.00 mm
 - 1 support MSA10.500-C
 - 1 lower support MSA10.505
 - 1 bracelet protector MSA10.500-E.



MSA	Size	Kg
10.499	60 x 80 x 110 mm	0.415

Press for fitting and removing the bracelet pins.
Simple version of press MSA10.500.

- Contents :
- 1 press and 1 broach MSA10.500-A
 - 1 bracelet holder MSA10.501
 - 6 pin punches MSA10.503-xxx : Ø 0.40, 0.60, 0.80, 1.00, 1.50 and 2.00 mm
 - 1 support MSA10.500-C.



Spare parts for MSA10.499 and MSA10.500 :

MSA	Item	Kg
10.499-03	Centering pin for base MSA10.499, Ø 4 x 17 mm	0.001
10.500-A	Broach for pin punch ; bore Ø 2 mm, length 80 mm	0.021
10.500-B	O-Ring gasket for broach MSA10.500-A (old version) and handle MSA10.504 ; Ø 3 mm, T 1.00	0.001
10.500-C	Support for the bracelet holder MSA10.501	0.003
10.500-D	Steel ball for broach MSA10.500-A and handle MSA10.504	0.001
10.500-E	Delrin® bracelet protector in slotted tulip shape	0.001
10.500-F	Maintaining ring (POM) of ball MSA10.500-D on broach MSA10.500-A	0.001
10.504	Knurled handle for blades MSA10.502-x ; length 84 mm	0.022
10.505	Lower support for blades MSA10.502-x and bracelet protector MSA10.500-E	0.013